



## ILLUMINATORS

[TPR Enterprises, Ltd. (914) 698-1141]

### 150 WATT DMX-64 METAL HALIDE FIBER OPTIC ILLUMINATOR SPECIFICATIONS



Click to Enlarge

#### UL LISTED

#### CURRENT:

4 AMPS

#### VOLTAGES:

120 VOLT 50-60 HZ  
220-240 VOLT 50-60 HZ

#### LAMP:

PHILIPS CDM-SA/R 150W/942  
LIFE HOURS 6000 AVERAGE  
COLOR TEMPERATURE 4200 K

#### SAFETY FEATURES:

INTERNAL THERMAL PROTECTOR  
140 F (Auto Reset)  
UV FILTER  
INPUT POWER FUSED

#### AMBIENT OPERATING TEMPERATURE:

20 F TO 110 F

#### FEATURES:

8 COLOR CHOICES  
VARIABLE SPEED TWINKLE (Utilizing Stepper Motor)  
ON BOARD DIMMING (MECHANICAL)  
VARIABLE SPEED COLOR SCROLL  
SPLIT COLOR CAPABILITY  
TWINKLE IS INDEPENDENT OF COLORS  
SUPERIOR LIGHT OUTPUT  
MOTORS ARE MICRO STEPPED ACHIEVING ULTRA SMOOTHNESS  
LAMP REPLACEMENT HATCH - NO TOOLS REQUIRED TO REPLACE LAMP  
SLEEP MODE  
DMX RESET  
XLR IN & OUT (3 pin)  
USES ONLY SIX DMX CHANNELS - EXTERNAL DMX ADDRESS

#### DIMENSIONS:

5 1/2" W x 8 1/2" H x 13" L  
(Including Exterior Motor)

#### WEIGHT:

14 LBS. □□

#### FINISH:

POWDER COATED BLACK

#### INSTALLATION:

INDOOR  
VERTICAL OR HORIZONTAL MOUNT  
(Including Bracket)

#### VENTILATION:

FORCED AIR 36 CFM X2  
12" CLEARANCE REQUIRED TO NEAREST SURFACE  
24" CLEARANCE REQUIRED BETWEEN EACH ILLUMINATOR

#### LAMP SOCKET:

QUICK CONNECT AMP CONNECTOR

#### WARRANTY:

ONE YEAR (Excluding Lamp)

**DESCRIPTION**

150 Watt Metal Halide DMX Addressable Fiber Optic Illuminator

[Instruction Manual](#) (79k PDF)

□

**CATALOG NUMBER**

**MODEL**  
[DMX-64-MH](#)

**POWER**  
[120V](#)  
[230V](#)

**COLOR WHEELS**  
[See Above](#)

**SYSTEM OPTIONS**  
[None](#)

TPR Enterprises, Ltd.  
644 Fayette Avenue  
Mamaroneck, New York 10543  
Phone: (914) 698-1141 Fax: (914) 698-9419  
[info@tprlights.com](mailto:info@tprlights.com)