



## ILLUMINATORS

[TPR Enterprises, Ltd. (914) 698-1141]

### 150 WATT DMX-64 FIBER OPTIC ILLUMINATOR SPECIFICATIONS



Click to Enlarge

#### UL LISTED

#### CURRENT:

3 AMPS

#### VOLTAGES:

120 VOLT 50-60 HZ  
220-240 VOLT 50-60 HZ

#### LAMP:

DDL 150 WATT 20 VOLT  
LIFE HOURS 500 AVERAGE  
COLOR TEMPERATURE 3150 K

#### SAFETY FEATURES:

INTERNAL THERMAL PROTECTOR  
140 F (Auto Reset)  
UV FILTER  
INPUT POWER FUSED

#### AMBIENT OPERATING TEMPERATURE:

20 F TO 110 F

#### FEATURES:

49 COLOR CHOICES PLUS CLEAR  
VARIABLE SPEED TWINKLE (Utilizing  
Stepper Motor)  
ON BOARD DIMMING  
VARIABLE SPEED COLOR SCROLL  
SPLIT COLOR CAPABILITY  
TWINKLE IS INDEPENDENT OF COLORS  
SUPERIOR LIGHT OUTPUT  
MOTORS ARE MICRO STEPPED ACHIEVING  
ULTRA SMOOTHNESS  
LAMP REPLACEMENT HATCH - NO TOOLS  
REQUIRED TO REPLACE LAMP  
SLEEP MODE  
DMX RESET  
XLR IN & OUT (3 pin)  
USES ONLY SIX DMX CHANNELS -  
EXTERNAL DMX ADDRESS

#### DIMENSIONS:

5 1/2" W x 8 1/2" H x 13" L  
(Including Exterior Motor)

#### WEIGHT:

13 LBS. □□

#### FINISH:

POWDER COATED BLACK

#### INSTALLATION:

INDOOR  
VERTICAL OR HORIZONTAL MOUNT  
(Including Bracket)

#### VENTILATION:

FORCED AIR 36 CFM X2  
12" CLEARANCE REQUIRED TO  
NEAREST SURFACE  
24" CLEARANCE REQUIRED  
BETWEEN EACH ILLUMINATOR

#### LAMP SOCKET:

HIGH QUALITY WITH INTEGRAL LAMP  
EJECTOR LEVER  
NICKEL PLATED CONTACTS

#### WARRANTY:

ONE YEAR (Excluding Lamp)

**DESCRIPTION**

150 Watt Halogen, DMX Addressable Fiber Optic Illuminator (Metal Halide version also available)

[Instruction Manual](#) (PDF)

□

**CATALOG NUMBER****MODEL**

[DMX-64](#)

**POWER**

[120V](#)  
[230V](#)

**COLOR WHEELS**

[See Above](#)

**SYSTEM OPTIONS**

[None](#)

TPR Enterprises, Ltd.  
644 Fayette Avenue  
Mamaroneck, New York 10543  
Phone: (914) 698-1141 Fax: (914) 698-9419  
[info@tprlights.com](mailto:info@tprlights.com)