



ILLUMINATORS

[TPR Enterprises, Ltd. (914) 698-1141]

150 WATT HIGH POWER FIBER OPTIC ILLUMINATOR SPECIFICATIONS



Click to Enlarge

UL LISTED

CURRENT:

1.5 AMPS

VOLTAGES:

120 VOLT 50-60 HZ
220-240 VOLT 50-60 HZ

LAMP:

DDL 150 WATT 20 VOLT
LIFE HOURS 175 AVERAGE
COLOR TEMPERATURE 3300 K

SAFETY FEATURES:

INTERNAL THERMAL PROTECTOR
140 F (Auto Reset)
UV FILTER
INPUT POWER FUSED

**AMBIENT OPERATING
TEMPERATURE:**

20 F TO 110 F

DIMENSIONS:

5" W x 4 1/2" H x 12 1/4" L
(Including Exterior Motor)

WEIGHT:

5 LBS. (DMX UNIT 11 LBS.)

FINISH:

POWDER COATED BLACK

INSTALLATION:

INDOOR
VERTICAL OR HORIZONTAL MOUNT

VENTILATION:

FORCED AIR 36 CFM
12" CLEARANCE REQUIRED TO
NEAREST SURFACE
24" CLEARANCE REQUIRED
BETWEEN EACH ILLUMINATOR

LAMP SOCKET:

HIGH QUALITY WITH INTEGRAL
LAMP EJECTOR LEVER

WARRANTY:

ONE YEAR (Excluding Lamp)

DESCRIPTION

150 Watt Halogen, 120 Volt AC, 60 Hz, Standard 5 Color Wheel, One power cord

CATALOG NUMBER

MODEL

TPR-FI-150-HP

POWER

120 - 120VAC, 60Hz

COLOR WHEELS

STD5T - Standard 5

SYSTEM OPTIONS

VS010 - Variable Speed 0-10V

150 Watt Halogen

230 - 230VAC, 50Hz
12 - 12 Volt DC

STD4S - Standard 4
STD3S - Standard 3
STD5S - Solid 5
TWBLA - Black Twinkle
TWBLU - Blue Twinkle
HDFL - High Density Flicker
SDFL - Standard Density Flicker
CHTW - Clear
CPHTW - Custom Painted
DICH - Dichroic
DICH3 - Three Color Dichroic
DICH4 - Four Color Dichroic
DICH5 - Five Color Dichroic

VS110 - Variable Speed 110
SYNCM - SYNC - Master
SYNCS - SYNC - Slave
DMX - DMX Addressable
PC1 - One Power Cord
PC2 - Two Power Cords
PC3 - Three Power Cords
EL - Extended Lamp

TPR Enterprises, Ltd.
644 Fayette Avenue
Mamaroneck, New York 10543
Phone: (914) 698-1141 Fax: (914) 698-9419
info@tprlights.com