



ILLUMINATORS

[TPR Enterprises, Ltd. (914) 698-1141]

150 WATT METAL HALIDE FIBER OPTIC ILLUMINATOR SPECIFICATIONS



Click to Enlarge

UL LISTED

CURRENT:

2 AMPS

VOLTAGES:

120 VOLT 60 HZ
240 VOLT 60 HZ
208 VOLT 60 HZ
277 VOLT 60 HZ
230 VOLT 50 HZ

LAMP:

PHILIPS CDM-SA/R 150W/942
LIFE HOURS 6000 AVERAGE
COLOR TEMPERATURE 4200° K

SAFETY FEATURES:

INTERNAL THERMAL PROTECTOR
140° F (Auto Reset)
UV FILTER
INPUT POWER FUSED
POWER SAFETY SWITCH

AMBIENT OPERATING TEMPERATURE:

20° F TO 110° F

DIMENSIONS:

7 1/2" W x 5 1/2" H x 14 1/4" L
(Including Exterior Motor)

WEIGHT:

18 LBS. □□ (DMX UNIT 20 LBS.)

FINISH:

POWDER COATED BLACK

INSTALLATION:

INDOOR
VERTICAL OR HORIZONTAL MOUNT

VENTILATION:

FORCED AIR 36 CFM
12" CLEARANCE REQUIRED TO
NEAREST SURFACE
24" CLEARANCE REQUIRED
BETWEEN EACH ILLUMINATOR

WARRANTY:

ONE YEAR (Excluding Lamp)

DESCRIPTION

150 Watt Metal Halide, 120 Volt AC, 60 Hz, Standard 5 Color Wheel, One power cord

[Instruction Manual](#) (65k PDF)

CATALOG NUMBER

MODEL

[TPR-FI-150-MH](#)
[150 Watt Metal Halide](#)

POWER

[120](#) - 120VAC, 60Hz
[230](#) - 230VAC, 50Hz
[12](#) - 12 Volt DC

COLOR WHEELS

[STD5T](#) - Standard 5
[STD4S](#) - Standard 4
[STD5S](#) - Standard 3
[STD5S](#) - Solid 5
[TWBLA](#) - Black Twinkle
[TWBLU](#) - Blue Twinkle
[HDFL](#) - High Density Flicker
[SDFL](#) - Standard Density Flicker
[CHTW](#) - Clear
[CPHTW](#) - Custom Painted
[DICH](#) - Dichroic

SYSTEM OPTIONS

[VS010](#) - Variable Speed 0-10V
[VS110](#) - Variable Speed 110V
[SYNCM](#) - SYNC - Master
[SYNCS](#) - SYNC - Slave
[DMX](#) - DMX Addressable
[PC1](#) - One Power Cord
[PC2](#) - Two Power Cords
[PC3](#) - Three Power Cords
[Q](#) - Osram Lamp

[DICH3](#) - Three Color Dichroic
[DICH4](#) - Four Color Dichroic
[DICH5](#) - Five Color Dichroic

TPR Enterprises, Ltd.
644 Fayette Avenue
Mamaroneck, New York 10543
Phone: (914) 698-1141 Fax: (914) 698-9419
info@tprlights.com