



ILLUMINATORS

[TPR Enterprises, Ltd. (914) 698-1141]

50 WATT FIBER OPTIC ILLUMINATOR SPECIFICATIONS*



Click to Enlarge

UL LISTED

CURRENT:

1 AMP

VOLTAGES:

120 VOLT 50-60 HZ
220-240 VOLT 50-60 HZ
12 VOLT AC OR DC

LAMP:

ENL 50 WATT 12 VOLT
LIFE HOURS 4000 AVERAGE
COLOR TEMPERATURE 3000 K

SAFETY FEATURES:

INTERNAL THERMAL PROTECTOR
140 F (Auto Reset)
UV FILTER
INPUT POWER FUSED

AMBIENT OPERATING TEMPERATURE:

20 F TO 110 F

DIMENSIONS:

5" W x 4 1/2" H x 12 1/4" L
(Including Exterior Motor)

WEIGHT:

5 LBS.

FINISH:

POWDER COATED BLACK

INSTALLATION:

INDOOR
VERTICAL OR HORIZONTAL MOUNT

VENTILATION:

FORCED AIR 36 CFM
12" CLEARANCE REQUIRED TO
NEAREST SURFACE
24" CLEARANCE REQUIRED
BETWEEN EACH ILLUMINATOR

LAMP SOCKET:

HIGH QUALITY WITH INTEGRAL
LAMP EJECTOR LEVER

WARRANTY:

ONE YEAR (Excluding Lamp)

* Specifications subject to change without notice.

DESCRIPTION

50 Watt Halogen, 120 Volt AC, 60 Hz, Standard 5 Color Wheel, One power cord

CATALOG NUMBER

MODEL

TPR-FI-50
50 WATT HALOGEN

POWER

120 - 120VAC, 60Hz
230 - 230 VAC, 50Hz

COLOR WHEELS

STD5T - Standard 5
STD45 - Standard 4

SYSTEM OPTIONS

VS010 - Variable Speed 0 - 10V

12 - 12 Volt DC

STD35 - Standard 3

STD5S - Solid 5

TWBLA - Black Twinkle

TWBLU - Blue Twinkle

HDFL - High Density Flicker

SDFL - Standard Density Flicker

CHTW - Clear

CPHTW - Custom Painted

DICH - Dichroic

DICH3 - Three Color Dichroic

DICH4 - Four Color Dichroic

DICH5 - Five Color Dichroic

VS110 - Variable Speed 110V

SYNCM - SYNC - Master

SYNCS - SYNC - Slave

DMX - DMX Addressable

PC1 - One Power Cord

PC2 - Two Power Cords

PC3 - Three Power Cords

TPR Enterprises, Ltd.
644 Fayette Avenue
Mamaroneck, New York 10543
Phone: (914) 698-1141 Fax: (914) 698-9419
info@tprlights.com