



TPR ENTERPRISES, LTD.®

MirageFlex™

Wet Location Instructions

These instructions are supplemental to the basic installation instructions.

MirageFlex™ Weatherproof Sheets are IP54 rated. IP54 means the following:

Protected against water splashed from all directions. This does not mean the product is waterproof. Moisture should not condensate and panel should not be exposed to water continuously. If these conditions exist, it will cause corrosion and product failure.

Cut Edges must be protected against water. This is accomplished by applying silicone sealant (available as an accessory from TPR). This also insulates the Panel from conductivity if mounted to a metal surface. Follow instructions on silicone packaging. You may use disposable gloves for this step. Coat the exposed cut areas with silicone. Do not cover LED as this will reduce light transmission and give an uneven appearance when lit.

Seal the edges while the protective backing is still on the back of the panel to avoid defeating adhesive properties. If the Panel is already mounted, you may apply silicone with no worries. Apply a small amount of silicone to finger and apply to cut edges. Remove any excess silicone.

Connectors must also be sealed with silicone. Apply silicone to connector and spread with finger. It is important to cover the entire connector and the first half inch of wire. Any unused connector must be sealed inside and out with silicone.

Sealing cut edges and connectors is imperative. Failure to cover all exposed areas will result in product failure.

If you have questions, call before you start (914) 698-1141.