

TPR WESTFLEX® 4-IN1 RGBW TAPELIGHT V2

IP20/67

Description:

The Westflex® 4-in1 RGBW V2
Tapelight is designed for Architectural and Entertainment markets. It is flexible, cuts to length every 1.96" and uses a high brightness 5050 LED for maximum performance. It is available in iindoor or outdoor (IP67 jackets, and is fully controllable via DMX512 when used in conjuction with the WestPower 300-4 DC Dimmer. The White quadrants of the LED chip are available in 2700K, 3000K, 4000K, and 6000K white



Specifications:

Lumens: 475 lm/ft (at full RGBW)

Power: 7.4 W/ft
Operating Voltage: 24VDC

Operating Temp: -4F to 104F (-20C to 40C)

Dimensions: 0.5"W x 0.2H


Max Run: 16.4' on Single Power Feed

Lamp Life: 50,000hrs @70% lumen maintenance

Max Lead: 35' with AWG18
Viewing Angle: 120 degrees
Cut Length: 1.96" (50mm)

Certifications:





Ordering Logic:

MODEL						PROTECTION (P) RATING
TPR-FL-SMD	-	RGBW4V2	-	2700K 3000K 4000K 6500K	-	NP (no jacket) IP (indoor protected) WP (weather protected)