





**TPR Akrobat™ Flexible LED Wall Grazer** is designed to provide high quality illumination for columns and curved architectural surfaces, with a variety of lens options that can be used for flood lighting, wall grazing, wall washing and accent lighting. This product is IP67 and operates on 24VDC. 4 meters can be connected end to end (13.12')

#### Dimension

L66\*W39\*H29mm



#### Bending





## Flexible LED Wall Grazer

- I. Flexible structure with continuous illumination without any shadows or dark areas.
- II. DC24V Input, can connect up to 4 meters together.
- III. Multiple lens options.
- IV. IP67, suitable for wet locations and has a protection rating of IK06.

## Product Application

Application areas: wall grazing, cove light, wall wash, residential, hospitality, restaurants, museums.

## Cover Styles



## Technical Parameters


Electrical	
Input Voltage	24V DC
Power Consumption	36W/m
Physical	
LED Count	18 LEDs/m (3.28')
Min. Unit	6 pcs LEDs/unit
Min. Unit Length	333 mm (1.09')
Housing Material	Aluminum + Tempered Glass Cover
Output	
LED Light	SMD LED 3030
Color	RGBW (3000K / 4000K / 6000K)
Working Mode	PWM
Max. Single Feed Length	4 M (13.12')
Optical Lens	15°, 20°, 30°, 40°, 60°, 10°x15°, 15°x30° 10°x45°, 15°x60°
Lumen Maintenance	70,000 Hours L70 @ 25°C 50,000 Hours L70 @ 50°C
Lumens per ft. @ 30°	140

Temperature Ranges	
Installation	0°C to 50°C (32°F – 122°F)
Operating	-25°C to 50°C (-13°F – 122°F)
Dependability	
Warranty	3 Years Warranty
IP Rating	IP67

# TPR Akrobat™ RGBW Flexible LED Wall Grazer



## Beam Spreads



## Ordering Code

TPR-FLWG - RGBW - - 1525 - A

Product No. \_\_\_\_\_

CCT & Color \_\_\_\_\_  
 RGBW (3000K), RGBW (4000K), RGBW (6000K)


Quantity of Units (increments of six units) \_\_\_\_\_

Lens Distribution \_\_\_\_\_  
 15=15° 20=20° 30=30° 40=40°  
 1015=10°x15° 1525=15°x25° 1540=15°x40° 2545=25°x45°


Cover Styles \_\_\_\_\_  
 A=Standard B=Honeycomb C=Anti Glare only available with 10°x15° lens

## Mounting Options

### Fixed Bracket



### Adjustable Bracket




# TPR Akrobat™ RGBW Flexible LED Wall Grazer





## Typical Minimum and Maximum Lengths

Min. L=333mm (1.09') (6xLED) 6 LED (12W)



Maximum Linking 48 LED 4000mm (13.12') (96W)




# TPR Akrobat™ RGBW Flexible LED Wall Grazer



## Typical Wiring and Control Options

---



## Accessories

---

TPR-FLWG-FB – Fixed Bracket  
TPR-FLWG-AB – Adjustable Bracket

TPR-FLWG-PC10 – 10' Power Cable  
TPR-FLWG-J1 – 1' Jumper  
TPR-FLWG-J3 – 3' Jumper