





**TPR Akrobat™ Flexible LED Wall Grazer** is designed to provide high quality illumination for columns and curved architectural surfaces, with a variety of lens options that can be used for flood lighting, wall grazing, wall washing and accent lighting. This product is IP20 and operates on 24VDC. 4 meters can be connected end to end (13.12')

#### Dimension

L66\*W39\*H29mm



#### Bending





## Flexible LED Wall Grazer

- I. Flexible structure with continuous illumination without any shadows or dark areas.
- II. DC24V Input, can connect up to 4 meters together.
- III. Multiple lens options.
- IV. IP20 for dry location only and has a protection rating of IK06.

## Product Application

Application areas: wall grazing, cove light, wall wash, residential, hospitality, restaurants, museums.

## Cover Styles




## Technical Parameters

| Electrical              |   |
|-------------------------|---|
| Input Voltage           | 24V DC  |
| Power Consumption       | 36W/m   |
| Physical                |   |
| LED Count               | 18 LEDs/m (3.28')   |
| Min. Unit               | 6 pcs LEDs/unit   |
| Min. Unit Length        | 333 mm (1.09')  |
| Housing Material        | Aluminum + Tempered Glass Cover                               |
| Output                  |   |
| LED Light               | SMD LED 3030  |
| Color                   | RGBW (3000K / 4000K / 6000K)                                  |
| Working Mode            | PWM   |
| Max. Single Feed Length | 4 M (13.12')  |
| Optical Lens            | 15°, 20°, 30°, 40°, 60°, 10°x15°, 15°x30°<br>10°x45°, 15°x60° |
| Lumen Maintenance       | 70,000 Hours L70 @ 25°C<br>50,000 Hours L70 @ 50°C            |
| Lumens per ft. @ 30°    | 140   |

| Temperature Ranges |                               |
|--------------------|-------------------------------|
| Installation       | 0°C to 50°C (32°F - 122°F)    |
| Operating          | -25°C to 50°C (-13°F - 122°F) |
| Dependability      |                               |
| Warranty           | 3 Years Warranty              |
| IP Rating          | IP20                          |

## Beam Spreads



## Ordering Code

TPR-FLWG - RGBW - - 1525 - A

Product No. \_\_\_\_\_

CCT & Color \_\_\_\_\_  
 RGBW (3000K), RGBW (4000K), RGBW (6000K)


Quantity of Units (increments of six units) \_\_\_\_\_

Lens Distribution \_\_\_\_\_  
 15=15° 20=20° 30=30° 40=40°  
 1015=10°x15° 1525=15°x25° 1540=15°x40° 2545=25°x45°


Cover Styles \_\_\_\_\_  
 A=Standard B=Honeycomb C=Anti Glare only available with 10°x15° lens

## Mounting Options

### Fixed Bracket



### Adjustable Bracket




# TPR Akrobat™ RGBW Flexible LED Wall Grazer





## Typical Minimum and Maximum Lengths

Min. L=333mm (1.09') (6xLED) 6 LED (12W)



Maximum Linking 48 LED 4000mm (13.12') (96W)




# TPR Akrobat™ RGBW Flexible LED Wall Grazer



## Typical Wiring and Control Options

---



## Accessories

---

TPR-FLWG-FB – Fixed Bracket  
TPR-FLWG-AB – Adjustable Bracket

TPR-FLWG-PC10 – 10' Power Cable  
TPR-FLWG-J1 – 1' Jumper  
TPR-FLWG-J3 – 3' Jumper