

TPR LINEAR FLOODLIGHT REFERENCE GUIDE

	DESCRIPTION	AVAILABLE CONFIGURATIONS	CONTROL
 <p>Illuzion V2 White</p>	<p>IP65 Linear Graze-Flood White Light, Low Profile 120-277 volt</p>	<p>1, 2 & 4ft. lengths. Various beam spreads, color temperatures & solid colors.</p>	<p>DMX/RDM 0-10</p>
 <p>Illuzion V2 RGBW</p>	<p>IP65 Linear Graze-Flood RGBW, Low Profile 120-277 volt</p>	<p>1, 2 & 4 ft. lengths. Various beam spreads & color temperatures for white. 4-channel or pixel addressing.</p>	<p>DMX/RDM</p>
 <p>Klarity White Weatherproof</p>	<p>IP66 Linear Graze-Flood White Light, Extremely Low Profile 120-277 volt</p>	<p>1, 2 & 4ft. lengths. Various beam spreads, color temperatures & solid colors.</p>	<p>DMX/RDM 0-10</p>
 <p>Klarity RGBW Weatherproof</p>	<p>IP66 Linear Graze-Flood RGBW, Extremely Low Profile 120-277 volt</p>	<p>1, 2 & 4ft. lengths. Various beam spreads & color temperatures for white.</p>	<p>DMX/RDM</p>

Specifications subject to change without notification.

TPR LINEAR FLOODLIGHT REFERENCE GUIDE

CONTINUED

	DESCRIPTION	AVAILABLE CONFIGURATIONS	CONTROL
 <p>Klarity White</p>	<p>IP20 Linear Graze-Flood White Light, Extremely Low Profile 120-277 volt</p>	<p>1, 2 & 4ft. lengths. Various beam spreads, color temperatures & solid colors</p>	<p>DMX/RDM 0-10</p>
 <p>Klarity RGBW</p>	<p>IP20 Linear Graze-Flood RGBW, Extremely Low Profile 120-277 volt</p>	<p>1, 2 & 4ft. lengths. Various beam spreads & color temperatures for white</p>	<p>DMX/RDM</p>
	<p>IP66 Direct View Linear Fixture, White Light 120-277 volt</p>	<p>1, 2 & 4 ft. lengths. Flat top or round top. Various color temperatures for white & solid colors</p>	<p>DMXRDM 0-10</p>
 <p>Illuzion V2 Direct View White</p>	<p>IP66 Direct View Linear Fixture, RGBW 120-277 volt</p>	<p>1, 2 & 4 ft. lengths. Flat top or round top. 4-channel or pixel addressing</p>	<p>DMXRDM</p>
 <p>Illuzion V2 Direct View RGBW</p>			

Specifications subject to change without notification.