TPR ENTERPRISES, LTD.®

TPR MIRAGE FLEX™ RGB PANEL

IP20

Description:

The **TPR Mirage Flex™ RGB** panel is extremely flexible, low profile and easy to install. It's field cuttable which makes it ideal for curved surfaces and applications where field modification is necessary. MirageFlex™ will provide even illumination with less than one inch of space between the light panel and the translucent material ie: stone, glass, polymer. Each sheet is provided with multiple quick connect points. This enables quick connection and feed through for multiple panels.

Specifications:

Voltage:	24V DC (CV)
Power Consumption:	25 watts per panel (@ full RGB)
Dimensions:	480mm x 240mm (18.90" x 9.45")
Segmentation:	Cutting increments every: 1.05" (26.7mm) L x 1.05" (26.7mm) W
Control:	DMX
Colors in Nanometers:	RED: 620-630nm GREEN: 520-525nm BLUE: 460-470nm
Lumens (by color):	RED: 230 lumens GREEN: 600 lumens BLUE: 155 lumens

Certifications:

UL® RoHS 2002/95/EC

Ordering Logic:

MODEL		WATTS (per panel)		RATING
TPR-MFLP-RGB	–	25W	–	IP20

168 Irving Ave, Suite 304F, Port Chester, NY 10573 | PHONE: 914.698.1141 | FAX: 914.305.1926 | E-MAIL: info@tprlights.com | www.tprlights.com

© TPR Enterprises, LTD.